



**Product Code . ILS-CL-11341**

## **Incubator 30L, upto 80C**

### **Description**

---

#### **Description:**

Temperature range 5°C above ambient up to 80°C

Temperature setting +20°C to +80°C; adjustment precision 0.1 K

Control COCKPIT, Single DISPLAY, and Adaptive multifunctional digital PID-microprocessor controller with high definition TFT-colour display.

User setting of temperature and time

Outer cabinet: Easy-to-clean stainless steel construction. Rear zinc-plated steel.

Electronic temperature monitoring and controlling

Maximum capacity: 32 Litres; with natural convection

Double wall construction for temperature insulation

Double door outside metal, inside made of tempered glass providing viewing of content

Micro-processor controlled stable temperature for culturing of media

**Power requirements:** 100V ~ 240V, 50/60Hz Function to stabilize power preventing unit from voltage surge accidentally.

Electronic on-off control, as well as a safety device against overheating

---

Unit fit with 3 shelves, adjustable height




Inner chamber, stainless steel

### **Intended use**

Incubator with the ability to hold certain temperature to incubate tests and samples

---

Indian Lab Suppliers,

Direct Contact Details  +91-8569909696  sales@indianlabsuppliers.com  
 [www.indianlabsuppliers.com](http://www.indianlabsuppliers.com)